

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Germany

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : CXX/R50-AM  
 Product code : 6501706  
 Trade name : CXX/R50-AM  
                   : ROT / RED  
 Index number :

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Colorant; Printing ink related material; Printing ink.	
Uses advised against	Reason
Not applicable.	

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/ Distributor** : SUN CHEMICAL  
 NORTON HILL  
 MIDSOMER NORTON  
 BATH  
 SOMERSET  
 BA3 4RT  
 UNITED KINGDOM  
 (44) 1689 894000  
  
 COATES SCREEN INKS GMBH  
 WIEDERHOLDPLATZ 1  
 D-90451 NURNBERG  
 GERMANY  
 (49) 911 6422 0  
  
**e-mail address of person responsible for this SDS** : regulatory.affairs@sunchemical.com

### 1.4 Emergency telephone number

**Supplier**

Telephone number :  
   (49) 911 6422 0 (7:30-16:00)  
   (49) 911 6422 299 (6:00am -20:00pm)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

**Classification according to Directive 1999/45/EC [DPD]**

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R10  
   Xi; R36

## SECTION 2: Hazards identification

**Physical/chemical hazards** : Flammable.


**Human health hazards** : Irritating to eyes.

See Section 16 for the full text of the R-phrases declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard symbol or symbols** :



**Indication of danger** : Irritant

**Risk phrases** : R10- Flammable.  
R36- Irritating to eyes.

**Safety phrases** : Not applicable.

**Supplemental label elements** : Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

### 2.3 Other hazards

**Other hazards which do not result in classification** : Not available.

## SECTION 3: Composition/information on ingredients

**Substance/mixture** : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
4-hydroxy-4-methylpentan-2-one	REACH #: 01-2119473975-21 EC: 204-626-7 CAS: 123-42-2 Index: 603-016-00-1	10 - 25	Xi; R36	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335	[1][2]
2-butoxyethyl acetate	REACH #: 01-2119475112-47 EC: 203-933-3 CAS: 112-07-2 Index: 607-038-00-2	10 - 25	Xn; R20/21	Acute Tox. 4, H312 Acute Tox. 4, H332	[1][2]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	10 - 25	R10	Flam. Liq. 3, H226 Eye Irrit. 2, H319	[2]
cyclohexanone	EC: 203-631-1 CAS: 108-94-1 Index: 606-010-00-7	5 - 10	R10 Xn; R20	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H332	[1][2]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	2.5 - 5	R10 R66, R67	Flam. Liq. 3, H226 STOT SE 3, H336	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2	1 - 2.5	R10 R67	Flam. Liq. 3, H226 STOT SE 3, H336	[1][2]

## SECTION 3: Composition/information on ingredients

Quaternary ammonium compounds, coco alkylethylidimethyl, Et sulfates	Index: 603-064-00-3 EC: 269-662-8 CAS: 68308-64-5	< 1	Xn; R22 Xi; R41, R38 N; R50	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400	[1]
(R)-p-mentha-1,8-diene	EC: 227-813-5 CAS: 5989-27-5 Index: 601-029-00-7	< 1	R10 Xi; R38 R43 N; R50/53  <b>See Section 16 for the full text of the R-phrases declared above.</b>	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410  <b>See Section 16 for the full text of the H statements declared above.</b>	[1][2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with room temperature water for at least 15 minutes, keeping eyelids open. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

## SECTION 4: First aid measures

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to medical doctor** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

**6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**6.3 Methods and materials for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Preferably clean with a detergent. Avoid using solvents.

## SECTION 7: Handling and storage

- 7.1 Precautions for safe handling** : Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.  
In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.  
To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.  
Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.  
Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8).  
Never use pressure to empty. Container is not a pressure vessel.  
Always keep in containers made from the same material as the original one.  
Comply with the health and safety at work laws.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 5 - 35 °C  
Store in accordance with local regulations.  
**Notes on joint storage**  
Keep away from: oxidizing agents, strong alkalis, strong acids.  
**Additional information on storage conditions**  
Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking.  
Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
- 7.3 Specific end use(s)**
- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
4-hydroxy-4-methylpentan-2-one	<b>TRGS900 AGW (Germany, 3/2011). Absorbed through skin.</b> PEAK: 192 mg/m <sup>3</sup> 15 minute(s). PEAK: 40 ppm 15 minute(s). TWA: 96 mg/m <sup>3</sup> 8 hour(s). TWA: 20 ppm 8 hour(s).
2-butoxyethyl acetate	<b>TRGS900 AGW (Germany, 3/2011). Absorbed through skin.</b> PEAK: 520 mg/m <sup>3</sup> 15 minute(s). PEAK: 80 ppm 15 minute(s). TWA: 130 mg/m <sup>3</sup> 8 hour(s). TWA: 20 ppm 8 hour(s).
2-methoxy-1-methylethyl acetate	<b>TRGS900 AGW (Germany, 3/2011).</b> PEAK: 270 mg/m <sup>3</sup> 15 minute(s). PEAK: 50 ppm 15 minute(s). TWA: 270 mg/m <sup>3</sup> 8 hour(s). TWA: 50 ppm 8 hour(s).
cyclohexanone	<b>TRGS900 AGW (Germany, 3/2011). Absorbed through skin.</b> PEAK: 80 mg/m <sup>3</sup> 15 minute(s).

## SECTION 8: Exposure controls/personal protection

1-methoxy-2-propanol	PEAK: 20 ppm 15 minute(s). TWA: 80 mg/m <sup>3</sup> 8 hour(s). TWA: 20 ppm 8 hour(s).
(R)-p-mentha-1,8-diene	<b>TRGS900 AGW (Germany, 3/2011).</b> PEAK: 740 mg/m <sup>3</sup> 15 minute(s). PEAK: 200 ppm 15 minute(s). TWA: 370 mg/m <sup>3</sup> 8 hour(s). TWA: 100 ppm 8 hour(s). <b>TRGS900 AGW (Germany, 3/2011). Skin sensitizer.</b> PEAK: 40 ppm 15 minute(s). PEAK: 220 mg/m <sup>3</sup> 15 minute(s). TWA: 20 ppm 8 hour(s). TWA: 110 mg/m <sup>3</sup> 8 hour(s).

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.
- Skin protection**
- Hand protection** : Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
- Gloves** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Body protection** : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state** : Liquid.
- Color** : Red.
- Odor** : Characteristic.
- Odor threshold** : Not applicable.
- Melting point/freezing point** : Not applicable.
- Flash point** : 27°C

## SECTION 9: Physical and chemical properties

<b>VOC</b>	: 66%
<b>pH</b>	: Not tested
<b>Lower explosion limit</b>	: Lower: 0.9% Upper: 13.1%
<b>Boiling point</b>	: Lowest known value: 120°C (248°F)
<b>Evaporation rate</b>	: Highest known value: 1 (n-butyl acetate) Weighted average: 0.23 compared with butyl acetate
<b>Upper/lower flammability or explosive limits</b>	: Not tested
<b>Vapor pressure</b>	: Not tested
<b>Vapor density</b>	: Not tested
<b>Relative density</b>	: Not tested
<b>Solubility(ies)</b>	: Not tested
<b>Partition coefficient: n-octanol/water</b>	: Not applicable.
<b>Auto-ignition temperature</b>	: Not applicable.
<b>Decomposition temperature</b>	: Not applicable.
<b>Viscosity</b>	: Not tested
<b>Explosive properties</b>	: Not applicable.
<b>Oxidizing properties</b>	: Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see section 7).
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

## SECTION 11: Toxicological information

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4-hydroxy-4-methylpentan-2-one	LD50 Dermal	Rabbit	13500 mg/kg	-
	LD50 Oral	Rat	2520 mg/kg	-
2-butoxyethyl acetate	LD50 Dermal	Rabbit	1500 mg/kg	-
	LD50 Oral	Rat	2400 mg/kg	-
2-methoxy-1-methylethyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	8532 mg/kg	-
cyclohexanone	LC50 Inhalation Gas.	Rat	8000 ppm	4 hours
	LD50 Oral	Rat	1800 mg/kg	-
n-butyl acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
1-methoxy-2-propanol	LD50 Oral	Rat	6600 mg/kg	-
	(R)-p-mentha-1,8-diene	LD50 Dermal	Rabbit	>5 g/kg
LD50 Oral		Rat	4400 mg/kg	-

#### Irritation/Corrosion

Not determined - Classification according to Directive 1999/45/EC [DPD]

#### Sensitization

Not determined - Classification according to Directive 1999/45/EC [DPD]

#### Mutagenicity

Not applicable.

#### Carcinogenicity

Not applicable.

#### Reproductive toxicity

Not determined - Classification according to Directive 1999/45/EC [DPD]

#### Teratogenicity

Not applicable.

## SECTION 12: Ecological information

There are no data available on the preparation itself.

Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment but contains a substance or substances dangerous for the environment. See section 3 for details.

### 12.1 Toxicity



## SECTION 12: Ecological information

4-hydroxy-4-methylpentan-2-one	Acute LC50 420000 ug/L Marine water	Fish - Menidia beryllina - 40 to 100 mm	96 hours
cyclohexanone	Acute LC50 527000 to 578000 ug/L Fresh water	Fish - Pimephales promelas - 30 days - 20.2 mm - 0.127 g	96 hours
n-butyl acetate	Acute LC50 32000 ug/L Marine water	Crustaceans - Artemia salina - Nauplii	48 hours
	Acute LC50 18000 to 19000 ug/L Fresh water	Fish - Pimephales promelas - 31 to 32 days - 21.6 mm - 0.175 g	96 hours
(R)-p-mentha-1,8-diene	Acute EC50 69600 ug/L Fresh water	Daphnia - Daphnia pulex - Neonate - <24 hours	48 hours
	Acute LC50 702 to 796 ug/L Fresh water	Fish - Pimephales promelas - 32 to 34 days - 21.8 mm - 0.177 g	96 hours

### 12.2 Persistence and degradability

Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
4-hydroxy-4-methylpentan-2-one	-0.14 to 1.03	-	low
2-butoxyethyl acetate	1.51	-	low
2-methoxy-1-methylethyl acetate	0.56	-	low
cyclohexanone	0.81	-	low
n-butyl acetate	1.78	-	low
(R)-p-mentha-1,8-diene	4.57	-	high

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

#### Packaging





## SECTION 13: Disposal considerations

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**European Waste Catalogue (EWC):** 08 03 12

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN/ADNR	IMDG	IATA
14.1 UN number	UN1210	UN1210	UN1210	UN1210
14.2 UN proper shipping name	PRINTING INK	PRINTING INK	PRINTING INK	PRINTING INK
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	<b>Special provisions</b> 640 (E)  <b>Tunnel code</b> (D/E)	-	-	-

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorization

Annex XVII - Restrictions : Not applicable.

on the manufacture,  
placing on the market and  
use of certain dangerous  
substances, mixtures and  
articles

#### Other EU regulations

#### National regulations

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**Hazardous incident ordinance** : Applicable. Category: 6 Flammable.

**Hazard class for water** : 2 Appendix No. 4

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still to be received.

## SECTION 16: Other information

**CEPE code** : 1

☑ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

**Full text of abbreviated H statements** : H226 Flammable liquid and vapor.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness and dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

**Full text of classifications [CLP/GHS]** : Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4  
Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4  
Aquatic Acute 1, H400 AQUATIC TOXICITY (ACUTE) - Category 1  
Aquatic Chronic 1, H410 AQUATIC TOXICITY (CHRONIC) - Category 1  
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE

**SECTION 16: Other information**

STOT SE 3, H336

EXPOSURE) [Respiratory tract irritation] - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE  
EXPOSURE) [Narcotic effects] - Category 3**Full text of abbreviated R phrases**

: R10- Flammable.  
 R20- Harmful by inhalation.  
 R22- Harmful if swallowed.  
 R20/21- Harmful by inhalation and in contact with skin.  
 R41- Risk of serious damage to eyes.  
 R36- Irritating to eyes.  
 R38- Irritating to skin.  
 R43- May cause sensitization by skin contact.  
 R66- Repeated exposure may cause skin dryness or cracking.  
 R67- Vapors may cause drowsiness and dizziness.  
 R50- Very toxic to aquatic organisms.  
 R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Full text of classifications [DSD/DPD]**

: Xn - Harmful  
 Xi - Irritant  
 N - Dangerous for the environment

**Date of printing**

: 4/15/2013.

**Date of issue/ Date of revision**

: 3/12/2013.

**Date of previous issue**

: No previous validation.

**Version**

: 0.01

**Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

**Annex**